


PACKAGING

STRETCH HOOD MACHINE HSA

- » Flexible use for different packaged goods, pallets and film types
- » Type HSA-Vario in different variations:
 - » single or double head design
 - » suitable for stretch as well as shrink film (HSA-Duo)
- » Patented end-of-film ejector device allows the film to be refilled without entering the safety area

- » Throughput rates with up to 120 hoods/h
- » Higher availability thanks to automatic film change with film ejector
- » Unrestricted use of films with recycled or high lubricant (slippery) content
- » Optimum transport safety through the use of maximum restoring forces
- » Short installation times and fast commissioning thanks to modular design of machine
- »  **PATENT**
 - » end-of-film ejector device



SPECIFICATIONS

- » Formats - All standard CP pallet formats (other dimensions on request)
- » Load height (max) 2,700 mm
- » Film thickness 40 µm – 160 µm (other film thickness on request)
- » PE side gusseted film

- » Use of vertical and horizontal stretch forces
- » Customized stretch geometry through driving mode by coordinates
- » With integrated profile control
- » Different types of stretch possible:
 - » banderole stretch
 - » high-bay warehouse stretch
 - » pallet understretch
 - » foot enforcement stretch
- » Wide range of optional designs:
 - » automatic changeover of up to two different types of film
 - » with upstream pallet press
 - » heating device for better film handling
 - » hydraulic bobbin changer

MARKETS



PETROCHEMICALS



FERTILIZER



CHEMICALS



FOOD



FEED



BUILDING MATERIALS

TAKE THE NEXT STEP TOWARDS EFFICIENCY

Talk to our experts to find out how our products can optimize your processes.

Fill out the contact form now and we will get in touch with you as soon as possible.

möllers
PACKAGING TECHNOLOGY GMBH

Möllers Packaging Technology GmbH | Rosalind-Franklin-Straße 2 | 59302 Oelde | Germany
Fon +49 2522 92018-0 | Mail sales@moellers.com | www.moellers.com



Scan the QR-Code to get in contact.